

Кабельные вводы с поддержкой кабеля



- Material: PA
- Seal piece: NBR & EPDM
- Protection class to: IP68
(tighten part, with O-seal ring)
- Temperature range:
static state -40°C to 100°C,
short time to 120°C,
motion state -20°C to 80°C,
short time to 100°C

Metric type cable glands -breakproof

Thread	∅mm	GLmm	Hmm	∅mm	AGmm
M12X1.5	3-6.5	8	65	16/17	12
M12X1.5	2-5	8	65	16/17	12
M14X1.5	4-8	8	70	19/20	14
M14X1.5	2-6	8	70	19/20	14
M16X1.5	4-8	8	70	19/20	16
M16X1.5	2-6	8	70	19/20	16
M16X1.5	5-10	8	78	22	16
M16X1.5	3-7	8	78	22	16
M18X1.5	5-10	8	78	22	18
M18X1.5	3-7	8	78	22	18
M20X1.5	6-12	9	90	24	20
M20X1.5	5-9	9	90	24	20
M20X1.5	10-14	10	100	27	20
M20X1.5	7-12	10	100	27	20
M22X1.5	10-14	10	100	27	22
M22X1.5	7-12	10	100	27	22
M25X1.5	13-18	10	112	33/34	25
M25X1.5	9-16	10	112	33/34	25
M27X1.5	13-18	10	112	33/34	27
M27X1.5	9-16	10	112	33/34	27

Metric type cable glands -breakproof & lengthen

Thread	∅mm	GLmm	Hmm	∅mm	AGmm
M12X1.5	3-6.5	15	65	16/17	12
M12X1.5	2-5	15	65	16/17	12
M16X1.5	4-8	15	70	19/20	16
M16X1.5	2-6	15	70	19/20	16
M16X1.5	5-10	15	78	22	16
M16X1.5	3-7	15	78	22	16
M18X1.5	5-10	15	78	22	18
M18X1.5	3-7	15	78	22	18
M20X1.5	6-12	15	90	24	20
M20X1.5	5-9	15	90	24	20
M20X1.5	10-14	15	100	27	20
M20X1.5	7-12	15	100	27	20
M22X1.5	10-14	15	100	27	22
M22X1.5	7-12	15	100	27	22
M25X1.5	13-18	15	112	33/34	25
M25X1.5	9-16	15	112	33/34	25
M27X1.5	13-18	15	112	33/34	27
M27X1.5	9-16	15	112	33/34	27

Dimension

