

MC7900 Series

1.0 A Negative Voltage Regulators

The MC7900 series of fixed output negative voltage regulators are intended as complements to the popular MC7800 series devices. These negative regulators are available in the same seven-voltage options as the MC7800 devices. In addition, one extra voltage option commonly employed in MECL systems is also available in the negative MC7900 series.

Available in fixed output voltage options from -5.0 V to -24 V , these regulators employ current limiting, thermal shutdown, and safe-area compensation – making them remarkably rugged under most operating conditions. With adequate heatsinking they can deliver output currents in excess of 1.0 A.

- No External Components Required
- Internal Thermal Overload Protection
- Internal Short Circuit Current Limiting
- Output Transistor Safe-Area Compensation
- Available in 2% Voltage Tolerance (See Ordering Information)
- Pb-Free Package May be Available. The G-Suffix Denotes a Pb-Free Lead Finish





Figure 1. Representative Schematic Diagram




ON Semiconductor®

<http://onsemi.com>




Pin 1. Ground
2. Input
3. Output



Heatsink surface (shown as terminal 4 in case outline drawing) is connected to Pin 2.

STANDARD APPLICATION



A common ground is required between the input and the output voltages. The input voltage must remain typically 2.0 V above more negative even during the high point of the input ripple voltage.

XX, These two digits of the type number indicate nominal voltage.

* C_{in} is required if regulator is located an appreciable distance from power supply filter.

** C_O improve stability and transient response.

ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 11 of this data sheet.

DEVICE MARKING INFORMATION

See general marking information in the device marking section on page 14 of this data sheet.

MC7900 Series

MAXIMUM RATINGS ($T_A = +25^\circ\text{C}$, unless otherwise noted.)

Rating	Symbol	Value	Unit
Input Voltage ($-5.0 \text{ V} \geq V_I \geq -18 \text{ V}$ (24 V)	V_I	-35 -40	Vdc
Power Dissipation Case 221A $T_A = +25^\circ\text{C}$ Thermal Resistance, Junction-to-Ambient Thermal Resistance, Junction-to-Case	P_D θ_{JA} θ_{JC}	Internally Limited 65 5.0	W °C/W °C/W
Case 936 (D ² PAK) $T_A = +25^\circ\text{C}$ Thermal Resistance, Junction-to-Ambient Thermal Resistance, Junction-to-Case	P_D θ_{JA} θ_{JC}	Internally Limited 70 5.0	W °C/W °C/W
Storage Junction Temperature Range	T_{stg}	-65 to +150	°C
Junction Temperature	T_J	+150	°C

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

*This device series contains ESD protection and exceeds the following tests:

Human Body Model 2000 V per MIL_STD_883, Method 3015
Machine Model Method 200 V

MC7905B, MC7905C

ELECTRICAL CHARACTERISTICS ($V_I = -10 \text{ V}$, $I_O = 500 \text{ mA}$, $T_{low}^* < T_J < +125^\circ\text{C}$, unless otherwise noted.)

Characteristics	Symbol	Min	Typ	Max	Unit
Output Voltage ($T_J = +25^\circ\text{C}$)	V_O	-4.8	-5.0	-5.2	Vdc
Line Regulation (Note 1) ($T_J = +25^\circ\text{C}$, $I_O = 100 \text{ mA}$) -7.0 Vdc $\geq V_I \geq -25 \text{ Vdc}$ -8.0 Vdc $\geq V_I \geq -12 \text{ Vdc}$ ($T_J = +25^\circ\text{C}$, $I_O = 500 \text{ mA}$) -7.0 Vdc $\geq V_I \geq -25 \text{ Vdc}$ -8.0 Vdc $\geq V_I \geq -12 \text{ Vdc}$	Reg_{line}	- - - -	7.0 2.0 35 8.0	50 25 100 50	mV
Load Regulation, $T_J = +25^\circ\text{C}$ (Note 1) $5.0 \text{ mA} \leq I_O \leq 1.5 \text{ A}$ $250 \text{ mA} \leq I_O \leq 750 \text{ mA}$	Reg_{load}	- -	11 4.0	100 50	mV
Output Voltage -7.0 Vdc $\geq V_I \geq -20 \text{ Vdc}$, $5.0 \text{ mA} \leq I_O \leq 1.0 \text{ A}$, $P \leq 15 \text{ W}$	V_O	-4.75	-	-5.25	Vdc
Input Bias Current ($T_J = +25^\circ\text{C}$)	I_{IB}	-	4.3	8.0	mA
Input Bias Current Change -7.0 Vdc $\geq V_I \geq -25 \text{ Vdc}$ $5.0 \text{ mA} \leq I_O \leq 1.5 \text{ A}$	ΔI_{IB}	- -	-	1.3 0.5	mA
Output Noise Voltage ($T_A = +25^\circ\text{C}$, $10 \text{ Hz} \leq f \leq 100 \text{ kHz}$)	V_n	-	40	-	µV
Ripple Rejection ($I_O = 20 \text{ mA}$, $f = 120 \text{ Hz}$)	RR	-	70	-	dB
Dropout Voltage $I_O = 1.0 \text{ A}$, $T_J = +25^\circ\text{C}$	$V_I - V_O$	-	1.3	-	Vdc
Average Temperature Coefficient of Output Voltage $I_O = 5.0 \text{ mA}$, $T_{low}^* \leq T_J \leq +125^\circ\text{C}$	$\Delta V_O / \Delta T$	-	-1.0	-	mV/°C

- Load and line regulation are specified at constant junction temperature. Changes in V_O due to heating effects must be taken into account separately. Pulse testing with low duty cycle is used.

* $T_{low} = -40^\circ\text{C}$ for MC7905B and $T_{low} = 0^\circ\text{C}$ for MC7905C.

MC7905AC**ELECTRICAL CHARACTERISTICS** ($V_I = -10$ V, $I_O = 500$ mA, $0^\circ\text{C} < T_J < +125^\circ\text{C}$, unless otherwise noted.)

Characteristics	Symbol	Min	Typ	Max	Unit
Output Voltage ($T_J = +25^\circ\text{C}$)	V_O	-4.9	-5.0	-5.1	Vdc
Line Regulation (Note 2) -8.0 Vdc $\geq V_I \geq -12$ Vdc; $I_O = 1.0$ A, $T_J = +25^\circ\text{C}$ -8.0 Vdc $\geq V_I \geq -12$ Vdc; $I_O = 1.0$ A -7.5 Vdc $\geq V_I \geq -25$ Vdc; $I_O = 500$ mA -7.0 Vdc $\geq V_I \geq -20$ Vdc; $I_O = 1.0$ A, $T_J = +25^\circ\text{C}$	Regline	-	2.0	25	mV
		-	7.0	50	
		-	7.0	50	
		-	6.0	50	
Load Regulation (Note 2) 5.0 mA $\leq I_O \leq 1.5$ A, $T_J = +25^\circ\text{C}$ 250 mA $\leq I_O \leq 750$ mA 5.0 mA $\leq I_O \leq 1.0$ A	Regload	-	11	100	mV
		-	4.0	50	
		-	9.0	100	
Output Voltage -7.5 Vdc $\geq V_I \geq -20$ Vdc, 5.0 mA $\leq I_O \leq 1.0$ A, $P \leq 15$ W	V_O	-4.80	-	-5.20	Vdc
Input Bias Current	I_{IB}	-	4.4	8.0	mA
Input Bias Current Change -7.5 Vdc $\geq V_I \geq -25$ Vdc 5.0 mA $\leq I_O \leq 1.0$ A 5.0 mA $\leq I_O \leq 1.5$ A, $T_J = +25^\circ\text{C}$	ΔI_{IB}	-	-	1.3	mA
		-	-	0.5	
		-	-	0.5	
Output Noise Voltage ($T_A = +25^\circ\text{C}$, 10 Hz $\leq f \leq 100$ kHz)	V_n	-	40	-	μV
Ripple Rejection ($I_O = 20$ mA, $f = 120$ Hz)	RR	-	70	-	dB
Dropout Voltage ($I_O = 1.0$ A, $T_J = +25^\circ\text{C}$)	$V_I - V_O$	-	1.3	-	Vdc
Average Temperature Coefficient of Output Voltage $I_O = 5.0$ A, $0^\circ\text{C} \leq T_J \leq +125^\circ\text{C}$	$\Delta V_O/\Delta T$	-	-1.0	-	mV/ $^\circ\text{C}$

MC7905.2C**ELECTRICAL CHARACTERISTICS** ($V_I = -10$ V, $I_O = 500$ mA, $0^\circ\text{C} < T_J < +125^\circ\text{C}$, unless otherwise noted.)

Characteristics	Symbol	Min	Typ	Max	Unit
Output Voltage ($T_J = +25^\circ\text{C}$)	V_O	-5.0	-5.2	-5.4	Vdc
Line Regulation (Note 2) ($T_J = +25^\circ\text{C}$, $I_O = 100$ mA) -7.2 Vdc $\geq V_I \geq -25$ Vdc -8.0 Vdc $\geq V_I \geq -12$ Vdc ($T_J = +25^\circ\text{C}$, $I_O = 500$ mA) -7.2 Vdc $\geq V_I \geq -25$ Vdc -8.0 Vdc $\geq V_I \geq -12$ Vdc	Regline	-	8.0	52	mV
		-	2.2	27	
		-	37	105	
		-	8.5	52	
Load Regulation, $T_J = +25^\circ\text{C}$ (Note 2) 5.0 mA $\leq I_O \leq 1.5$ A 250 mA $\leq I_O \leq 750$ mA	Regload	-	12	105	mV
		-	4.5	52	
Output Voltage -7.2 Vdc $\geq V_I \geq -20$ Vdc, 5.0 mA $\leq I_O \leq 1.0$ A, $P \leq 15$ W	V_O	-4.95	-	-5.45	Vdc
Input Bias Current ($T_J = +25^\circ\text{C}$)	I_{IB}	-	4.3	8.0	mA
Input Bias Current Change -7.2 Vdc $\geq V_I \geq -25$ Vdc 5.0 mA $\leq I_O \leq 1.5$ A	ΔI_{IB}	-	-	1.3	mA
		-	-	0.5	
Output Noise Voltage ($T_A = +25^\circ\text{C}$, 10 Hz $\leq f \leq 100$ kHz)	V_n	-	42	-	μV
Ripple Rejection ($I_O = 20$ mA, $f = 120$ Hz)	RR	-	68	-	dB
Dropout Voltage ($I_O = 1.0$ A, $T_J = +25^\circ\text{C}$)	$V_I - V_O$	-	1.3	-	Vdc
Average Temperature Coefficient of Output Voltage $I_O = 5.0$ mA, $0^\circ\text{C} \leq T_J \leq +125^\circ\text{C}$	$\Delta V_O/\Delta T$	-	-1.0	-	mV/ $^\circ\text{C}$

2. Load and line regulation are specified at constant junction temperature. Changes in V_O due to heating effects must be taken into account separately. Pulse testing with low duty cycle is used.

MC7906C

ELECTRICAL CHARACTERISTICS ($V_I = -11\text{ V}$, $I_O = 500\text{ mA}$, $0^\circ\text{C} < T_J < +125^\circ\text{C}$, unless otherwise noted.)

Characteristics	Symbol	Min	Typ	Max	Unit
Output Voltage ($T_J = +25^\circ\text{C}$)	V_O	-5.75	-6.0	-6.25	Vdc
Line Regulation (Note 3) ($T_J = +25^\circ\text{C}$, $I_O = 100\text{ mA}$) -8.0 Vdc $\geq V_I \geq$ -25 Vdc -9.0 Vdc $\geq V_I \geq$ -13 Vdc ($T_J = +25^\circ\text{C}$, $I_O = 500\text{ mA}$) -8.0 Vdc $\geq V_I \geq$ -25 Vdc -9.0 Vdc $\geq V_I \geq$ -13 Vdc	Regline	-	9.0 3.0	60 30	mV
Load Regulation, $T_J = +25^\circ\text{C}$ (Note 3) $5.0\text{ mA} \leq I_O \leq 1.5\text{ A}$ $250\text{ mA} \leq I_O \leq 750\text{ mA}$	Regload	-	13 5.0	120 60	mV
Output Voltage -8.0 Vdc $\geq V_I \geq$ -21 Vdc, $5.0\text{ mA} \leq I_O \leq 1.0\text{ A}$, $P \leq 15\text{ W}$	V_O	-5.7	-	-6.3	Vdc
Input Bias Current ($T_J = +25^\circ\text{C}$)	I_{IB}	-	4.3	8.0	mA
Input Bias Current Change -8.0 Vdc $\geq V_I \geq$ -25 Vdc $5.0\text{ mA} \leq I_O \leq 1.5\text{ A}$	ΔI_{IB}	-	-	1.3 0.5	mA
Output Noise Voltage ($T_A = +25^\circ\text{C}$, $10\text{ Hz} \leq f \leq 100\text{ kHz}$)	V_n	-	45	-	μV
Ripple Rejection ($I_O = 20\text{ mA}$, $f = 120\text{ Hz}$)	RR	-	65	-	dB
Dropout Voltage ($I_O = 1.0\text{ A}$, $T_J = +25^\circ\text{C}$)	$V_I - V_O$	-	1.3	-	Vdc
Average Temperature Coefficient of Output Voltage $I_O = 5.0\text{ A}$, $0^\circ\text{C} \leq T_J \leq +125^\circ\text{C}$	$\Delta V_O/\Delta T$	-	-1.0	-	$\text{mV}/^\circ\text{C}$

MC7908C

ELECTRICAL CHARACTERISTICS ($V_I = -14\text{ V}$, $I_O = 500\text{ mA}$, $0^\circ\text{C} < T_J < +125^\circ\text{C}$, unless otherwise noted.)

Characteristics	Symbol	Min	Typ	Max	Unit
Output Voltage ($T_J = +25^\circ\text{C}$)	V_O	-7.7	-8.0	-8.3	Vdc
Line Regulation (Note 3) ($T_J = +25^\circ\text{C}$, $I_O = 100\text{ mA}$) -10.5 Vdc $\geq V_I \geq$ -25 Vdc -11 Vdc $\geq V_I \geq$ -17 Vdc ($T_J = +25^\circ\text{C}$, $I_O = 500\text{ mA}$) -10.5 Vdc $\geq V_I \geq$ -25 Vdc -11 Vdc $\geq V_I \geq$ -17 Vdc	Regline	-	12 5.0	80 40	mV
Load Regulation, $T_J = +25^\circ\text{C}$ (Note 3) $5.0\text{ mA} \leq I_O \leq 1.5\text{ A}$ $250\text{ mA} \leq I_O \leq 750\text{ mA}$	Regload	-	26 9.0	160 80	mV
Output Voltage -10.5 Vdc $\geq V_I \geq$ -23 Vdc, $5.0\text{ mA} \leq I_O \leq 1.0\text{ A}$, $P \leq 15\text{ W}$	V_O	-7.6	-	-8.4	Vdc
Input Bias Current ($T_J = +25^\circ\text{C}$)	I_{IB}	-	4.3	8.0	mA
Input Bias Current Change -10.5 Vdc $\geq V_I \geq$ -25 Vdc $5.0\text{ mA} \leq I_O \leq 1.5\text{ A}$	ΔI_{IB}	-	-	1.0 0.5	mA
Output Noise Voltage ($T_A = +25^\circ\text{C}$, $10\text{ Hz} \leq f \leq 100\text{ kHz}$)	V_n	-	52	-	μV
Ripple Rejection ($I_O = 20\text{ mA}$, $f = 120\text{ Hz}$)	RR	-	62	-	dB
Dropout Voltage ($I_O = 1.0\text{ A}$, $T_J = +25^\circ\text{C}$)	$V_I - V_O$	-	1.3	-	Vdc
Average Temperature Coefficient of Output Voltage $I_O = 5.0\text{ mA}$, $0^\circ\text{C} \leq T_J \leq +125^\circ\text{C}$	$\Delta V_O/\Delta T$	-	-1.0	-	$\text{mV}/^\circ\text{C}$

3. Load and line regulation are specified at constant junction temperature. Changes in V_O due to heating effects must be taken into account separately. Pulse testing with low duty cycle is used.

MC7912B, MC7912C
ELECTRICAL CHARACTERISTICS ($V_I = -19$ V, $I_O = 500$ mA, $T_{low}^* < T_J < +125^\circ\text{C}$, unless otherwise noted.)

Characteristics	Symbol	Min	Typ	Max	Unit
Output Voltage ($T_J = +25^\circ\text{C}$)	V_O	-11.5	-12	-12.5	Vdc
Line Regulation (Note 4) ($T_J = +25^\circ\text{C}$, $I_O = 100$ mA) -14.5 Vdc $\geq V_I \geq -30$ Vdc -16 Vdc $\geq V_I \geq -22$ Vdc ($T_J = +25^\circ\text{C}$, $I_O = 500$ mA) -14.5 Vdc $\geq V_I \geq -30$ Vdc -16 Vdc $\geq V_I \geq -22$ Vdc	Reg_{line}	-	13 6.0	120 60	mV
Load Regulation, $T_J = +25^\circ\text{C}$ (Note 4) 5.0 mA $\leq I_O \leq 1.5$ A 250 mA $\leq I_O \leq 750$ mA	Reg_{load}	-	46 17	240 120	mV
Output Voltage -14.5 Vdc $\geq V_I \geq -27$ Vdc, 5.0 mA $\leq I_O \leq 1.0$ A, $P \leq 15$ W	V_O	-11.4	-	-12.6	Vdc
Input Bias Current ($T_J = +25^\circ\text{C}$)	I_{IB}	-	4.4	8.0	mA
Input Bias Current Change -14.5 Vdc $\geq V_I \geq -30$ Vdc 5.0 mA $\leq I_O \leq 1.5$ A	ΔI_{IB}	-	-	1.0 0.5	mA
Output Noise Voltage ($T_A = +25^\circ\text{C}$, 10 Hz $\leq f \leq 100$ kHz)	V_n	-	75	-	μV
Ripple Rejection ($I_O = 20$ mA, $f = 120$ Hz)	RR	-	61	-	dB
Dropout Voltage ($I_O = 1.0$ A, $T_J = +25^\circ\text{C}$)	$V_I - V_O$	-	1.3	-	Vdc
Average Temperature Coefficient of Output Voltage $I_O = 5.0$ mA, $T_{low}^* \leq T_J \leq +125^\circ\text{C}$	$\Delta V_O/\Delta T$	-	-1.0	-	mV/ $^\circ\text{C}$

MC7912AC
ELECTRICAL CHARACTERISTICS ($V_I = -19$ V, $I_O = 500$ mA, $T_{low}^* < T_J < +125^\circ\text{C}$, unless otherwise noted.)

Characteristics	Symbol	Min	Typ	Max	Unit
Output Voltage ($T_J = +25^\circ\text{C}$)	V_O	-11.75	-12	-12.25	Vdc
Line Regulation (Note 4) -16 Vdc $\geq V_I \geq -22$ Vdc; $I_O = 1.0$ A, $T_J = +25^\circ\text{C}$ -16 Vdc $\geq V_I \geq -22$ Vdc; $I_O = 1.0$ A -14.8 Vdc $\geq V_I \geq -30$ Vdc; $I_O = 500$ mA -14.5 Vdc $\geq V_I \geq -27$ Vdc; $I_O = 1.0$ A, $T_J = +25^\circ\text{C}$	Reg_{line}	-	6.0 24 24 13	60 120 120 120	mV
Load Regulation (Note 4) 5.0 mA $\leq I_O \leq 1.5$ A, $T_J = +25^\circ\text{C}$ 250 mA $\leq I_O \leq 750$ mA 5.0 mA $\leq I_O \leq 1.0$ A	Reg_{load}	-	46 17 35	150 75 150	mV
Output Voltage -14.8 Vdc $\geq V_I \geq -27$ Vdc, 5.0 mA $\leq I_O \leq 1.0$ A, $P \leq 15$ W	V_O	-11.5	-	-12.5	Vdc
Input Bias Current	I_{IB}	-	4.4	8.0	mA
Input Bias Current Change -15 Vdc $\geq V_I \geq -30$ Vdc 5.0 mA $\leq I_O \leq 1.0$ A 5.0 mA $\leq I_O \leq 1.5$ A, $T_J = +25^\circ\text{C}$	ΔI_{IB}	-	-	0.8 0.5 0.5	mA
Output Noise Voltage ($T_A = +25^\circ\text{C}$, 10 Hz $\leq f \leq 100$ kHz)	V_n	-	75	-	μV
Ripple Rejection ($I_O = 20$ mA, $f = 120$ Hz)	RR	-	61	-	dB
Dropout Voltage ($I_O = 1.0$ A, $T_J = +25^\circ\text{C}$)	$V_I - V_O$	-	1.3	-	Vdc
Average Temperature Coefficient of Output Voltage $I_O = 5.0$ A, $T_{low}^* \leq T_J \leq +125^\circ\text{C}$	$\Delta V_O/\Delta T$	-	-1.0	-	mV/ $^\circ\text{C}$

4. Load and line regulation are specified at constant junction temperature. Changes in V_O due to heating effects must be taken into account separately. Pulse testing with low duty cycle is used.

*Tlow = -40°C for MC7912B and Tlow = 0°C for MC7912C.

MC7915B, MC7915C
ELECTRICAL CHARACTERISTICS ($V_I = -23$ V, $I_O = 500$ mA, $T_{low}^* < T_J < +125^\circ\text{C}$, unless otherwise noted.)

Characteristics	Symbol	Min	Typ	Max	Unit
Output Voltage ($T_J = +25^\circ\text{C}$)	V_O	-14.4	-15	-15.6	Vdc
Line Regulation (Note 5) ($T_J = +25^\circ\text{C}$, $I_O = 100$ mA) -17.5 Vdc $\geq V_I \geq$ -30 Vdc -20 Vdc $\geq V_I \geq$ -26 Vdc ($T_J = +25^\circ\text{C}$, $I_O = 500$ mA) -17.5 Vdc $\geq V_I \geq$ -30 Vdc -20 Vdc $\geq V_I \geq$ -26 Vdc	Regline	- - - -	14 6.0 57 27	150 75 300 150	mV
Load Regulation, $T_J = +25^\circ\text{C}$ (Note 5) 5.0 mA $\leq I_O \leq 1.5$ A 250 mA $\leq I_O \leq 750$ mA	Regload	- -	68 25	300 150	mV
Output Voltage -17.5 Vdc $\geq V_I \geq$ -30 Vdc, 5.0 mA $\leq I_O \leq 1.0$ A, $P \leq 15$ W	V_O	-14.25	-	-15.75	Vdc
Input Bias Current ($T_J = +25^\circ\text{C}$)	I_{IB}	-	4.4	8.0	mA
Input Bias Current Change -17.5 Vdc $\geq V_I \geq$ -30 Vdc 5.0 mA $\leq I_O \leq 1.5$ A	ΔI_{IB}	- -	-	1.0 0.5	mA
Output Noise Voltage ($T_A = +25^\circ\text{C}$, 10 Hz $\leq f \leq 100$ kHz)	V_n	-	90	-	µV
Ripple Rejection ($I_O = 20$ mA, $f = 120$ Hz)	RR	-	60	-	dB
Dropout Voltage ($I_O = 1.0$ A, $T_J = +25^\circ\text{C}$)	$V_I - V_O$	-	1.3	-	Vdc
Average Temperature Coefficient of Output Voltage $I_O = 5.0$ A, $T_{low}^* \leq T_J \leq +125^\circ\text{C}$	$\Delta V_O / \Delta T$	-	-1.0	-	mV/°C

MC7915AC
ELECTRICAL CHARACTERISTICS ($V_I = -23$ V, $I_O = 500$ mA, $T_{low}^* < T_J < +125^\circ\text{C}$, unless otherwise noted.)

Characteristics	Symbol	Min	Typ	Max	Unit
Output Voltage ($T_J = +25^\circ\text{C}$)	V_O	-14.7	-15	-15.3	Vdc
Line Regulation (Note 5) -20 Vdc $\geq V_I \geq$ -26 Vdc, $I_O = 1.0$ A, $T_J = +25^\circ\text{C}$ -20 Vdc $\geq V_I \geq$ -26 Vdc, $I_O = 1.0$ A, -17.9 Vdc $\geq V_I \geq$ -30 Vdc, $I_O = 500$ mA -17.5 Vdc $\geq V_I \geq$ -30 Vdc, $I_O = 1.0$ A, $T_J = +25^\circ\text{C}$	Regline	- - - -	27 57 57 57	75 150 150 150	mV
Load Regulation (Note 5) 5.0 mA $\leq I_O \leq 1.5$ A, $T_J = +25^\circ\text{C}$ 250 mA $\leq I_O \leq 750$ mA 5.0 mA $\leq I_O \leq 1.0$ A	Regload	- - -	68 25 40	150 75 150	mV
Output Voltage -17.9 Vdc $\geq V_I \geq$ -30 Vdc, 5.0 mA $\leq I_O \leq 1.0$ A, $P \leq 15$ W	V_O	-14.4	-	-15.6	Vdc
Input Bias Current	I_{IB}	-	4.4	8.0	mA
Input Bias Current Change -17.5 Vdc $\geq V_I \geq$ -30 Vdc 5.0 mA $\leq I_O \leq 1.0$ A 5.0 mA $\leq I_O \leq 1.5$ A, $T_J = +25^\circ\text{C}$	ΔI_{IB}	- - -	-	0.8 0.5 0.5	mA
Output Noise Voltage ($T_A = +25^\circ\text{C}$, 10 Hz $\leq f \leq 100$ kHz)	V_n	-	90	-	µV
Ripple Rejection ($I_O = 20$ mA, $f = 120$ Hz)	RR	-	60	-	dB
Dropout Voltage ($I_O = 1.0$ A, $T_J = +25^\circ\text{C}$)	$V_I - V_O$	-	1.3	-	Vdc
Average Temperature Coefficient of Output Voltage $I_O = 5.0$ mA, $T_{low}^* \leq T_J \leq +125^\circ\text{C}$	$\Delta V_O / \Delta T$	-	-1.0	-	mV/°C

5. Load and line regulation are specified at constant junction temperature. Changes in V_O due to heating effects must be taken into account separately. Pulse testing with low duty cycle is used.

* $T_{low} = -40^\circ\text{C}$ for MC7915B and $T_{low} = 0^\circ\text{C}$ for MC7915C.

MC7918C

ELECTRICAL CHARACTERISTICS ($V_I = -27 \text{ V}$, $I_O = 500 \text{ mA}$, $0^\circ\text{C} < T_J < +125^\circ\text{C}$, unless otherwise noted.)

Characteristics	Symbol	Min	Typ	Max	Unit
Output Voltage ($T_J = +25^\circ\text{C}$)	V_O	-17.3	-18	-18.7	Vdc
Line Regulation (Note 6) ($T_J = +25^\circ\text{C}$, $I_O = 100 \text{ mA}$) -21 Vdc $\geq V_I \geq$ -33 Vdc -24 Vdc $\geq V_I \geq$ -30 Vdc ($T_J = +25^\circ\text{C}$, $I_O = 500 \text{ mA}$) -21 Vdc $\geq V_I \geq$ -33 Vdc -24 Vdc $\geq V_I \geq$ -30 Vdc	Regline	- - - -	25 10 90 50	180 90 360 180	mV
Load Regulation, $T_J = +25^\circ\text{C}$ (Note 6) $5.0 \text{ mA} \leq I_O \leq 1.5 \text{ A}$ $250 \text{ mA} \leq I_O \leq 750 \text{ mA}$	Regload	- -	110 55	360 180	mV
Output Voltage -21 Vdc $\geq V_I \geq$ -33 Vdc, $5.0 \text{ mA} \leq I_O \leq 1.0 \text{ A}$, $P \leq 15 \text{ W}$	V_O	-17.1	-	-18.9	Vdc
Input Bias Current ($T_J = +25^\circ\text{C}$)	I_{IB}	-	4.5	8.0	mA
Input Bias Current Change -21 Vdc $\geq V_I \geq$ -33 Vdc $5.0 \text{ mA} \leq I_O \leq 1.5 \text{ A}$	ΔI_{IB}	- -	- -	1.0 0.5	mA
Output Noise Voltage ($T_A = +25^\circ\text{C}$, $10 \text{ Hz} \leq f \leq 100 \text{ kHz}$)	V_n	-	110	-	μV
Ripple Rejection ($I_O = 20 \text{ mA}$, $f = 120 \text{ Hz}$)	RR	-	59	-	dB
Dropout Voltage ($I_O = 1.0 \text{ A}$, $T_J = +25^\circ\text{C}$)	$V_I - V_O$	-	1.3	-	Vdc
Average Temperature Coefficient of Output Voltage $I_O = 5.0 \text{ mA}$, $0^\circ\text{C} \leq T_J \leq +125^\circ\text{C}$	$\Delta V_O/\Delta T$	-	-1.0	-	$\text{mV}/^\circ\text{C}$

MC7924B, MC7924C

ELECTRICAL CHARACTERISTICS ($V_I = -33 \text{ V}$, $I_O = 500 \text{ mA}$, $T_{low^*} < T_J < +125^\circ\text{C}$, unless otherwise noted.)

Characteristics	Symbol	Min	Typ	Max	Unit
Output Voltage ($T_J = +25^\circ\text{C}$)	V_O	-23	-24	-25	Vdc
Line Regulation (Note 6) ($T_J = +25^\circ\text{C}$, $I_O = 100 \text{ mA}$) -27 Vdc $\geq V_I \geq$ -38 Vdc -30 Vdc $\geq V_I \geq$ -36 Vdc ($T_J = +25^\circ\text{C}$, $I_O = 500 \text{ mA}$) -27 Vdc $\geq V_I \geq$ -38 Vdc -30 Vdc $\geq V_I \geq$ -36 Vdc	Regline	- - - -	31 14 118 70	240 120 470 240	mV
Load Regulation, $T_J = +25^\circ\text{C}$ (Note 6) $5.0 \text{ mA} \leq I_O \leq 1.5 \text{ A}$ $250 \text{ mA} \leq I_O \leq 750 \text{ mA}$	Regload	- -	150 85	480 240	mV
Output Voltage -27 Vdc $\geq V_I \geq$ -38 Vdc, $5.0 \text{ mA} \leq I_O \leq 1.0 \text{ A}$, $P \leq 15 \text{ W}$	V_O	-22.8	-	-25.2	Vdc
Input Bias Current ($T_J = +25^\circ\text{C}$)	I_{IB}	-	4.6	8.0	mA
Input Bias Current Change -27 Vdc $\geq V_I \geq$ -38 Vdc $5.0 \text{ mA} \leq I_O \leq 1.5 \text{ A}$	ΔI_{IB}	- -	- -	1.0 0.5	mA
Output Noise Voltage ($T_A = +25^\circ\text{C}$, $10 \text{ Hz} \leq f \leq 100 \text{ kHz}$)	V_n	-	170	-	μV
Ripple Rejection ($I_O = 20 \text{ mA}$, $f = 120 \text{ Hz}$)	RR	-	56	-	dB
Dropout Voltage ($I_O = 1.0 \text{ A}$, $T_J = +25^\circ\text{C}$)	$V_I - V_O$	-	1.3	-	Vdc
Average Temperature Coefficient of Output Voltage $I_O = 5.0 \text{ mA}$, $T_{low^*} \leq T_J \leq +125^\circ\text{C}$	$\Delta V_O/\Delta T$	-	-1.0	-	$\text{mV}/^\circ\text{C}$

6. Load and line regulation are specified at constant junction temperature. Changes in V_O due to heating effects must be taken into account separately. Pulse testing with low duty cycle is used.

* $T_{low} = -40^\circ\text{C}$ for MC7924B and $T_{low} = 0^\circ\text{C}$ for MC7924C.