

FYISS-1204BHR/YGC

Radiation pattern.

Features:


- Compatible with automatic placement equipment
- Compatible with reflow solder process.

Applications:

- Automotive-Telecommunication.
- Indicators.
- Lcd Back-lights.
- Illuminations.

Descriptions:

- Dice material: R: AlGaAs.
G: AlGaAs.
- Emitting Color: R: Red.
G: Green
- Lens Color: Water clear.








Absolute maximum ratings($T_a = 25^\circ \text{C}$)

Parameter	MAX.	Unit
Power Dissipation	50	mW
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width)	100	mA
Continuous Forward Current	30	mA
Derating Linear From 25°C	0.4	mA/ $^\circ \text{C}$
Operating Temperature Range	-30°C to $+85^\circ \text{C}$	
Storage Temperature Range	-40°C to $+85^\circ \text{C}$	

Electrical and optical characteristics($T_a = 25^\circ \text{C}$)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Condition
Luminous Intensity	IV	R	--	10	--	IF=20mA
		G	--	15	--	
Viewing Angle	$2\theta_{1/2}$	100	110	120	Deg	
Peak Emission Wavelength	λ_p	R	655	660	665	
		G	565	570	575	
Dominant Wavelength	λ_d	R	635	640	645	
		G	566	571	576	
Spectral Line Half-Width	$\Delta \lambda$	25	30	35	nm	
Forward Voltage	VF	R	--	2.1	2.4	
		G	--	2.3	2.4	
Reverse Current	IR			10	A	VR=5V

Typical Electrical Characteristics Curves (25°C Ambient Temperature Unless Otherwise Noted)



Precautions For Use

Over-current-proof

Customer must apply resistors for protection, otherwise slight voltage shift will cause big current change (Burn out will happen)

Storage


1. The operation of temperature and R.H are: $5^{\circ}\text{C} \sim 30^{\circ}\text{C}$, R.H. 60% Max.
2. Once the package is opened, the products should be used within a week. Otherwise, they should be kept in a dampproof box with desiccating reagent. Considering the tape life, we suggest our customers to use our products within 1.5 year (from production date).
3. It's recommended to bake before soldering when the package is unsealed after 72hrs. The condition is: $60^{\circ}\text{C} \pm 5^{\circ}\text{C}$ for 15 hrs.

Soldering Iron:


Temperature at tip of iron: 300°C Max. (25W Max)

Soldering time: 3 ± 1 sec.

Reflow Temp./Time:




Package Dimensions of Device




Tape Specification: 3000pcs Per Reel.



Packing Size								
Item	W	P1	E	F	D0	D1	P0	Unit
Spec.	8.00	4.00	1.75	3.50	1.50	1.00	4.00	mm
Tolerance	±0.20	±0.10	±0.10	±0.05	+0.1/-0	±0.05	±0.05	mm
Item	10P0	P2	A0	B0	K0	T		Unit
Spec.	40.00	2.00	2.80	3.35	1.65	0.23		mm
Tolerance	±0.20	±0.05	±0.10	±0.10	±0.10	±0.05		mm



Package Dimensions of Reel:



Packing and Shipping Spec.



CARTON
Dimension(cm):39*32*38

