

REVISION RECORD

REV	ECN	DESCRIPTION	DRFT	DATE
-----	-----	-------------	------	------

NOTES1:

UL Standard

- 1.Rated voltage/current : 300V / 20A
- 2.Torque value : M3.5 , 7.02Lb.in
- 3.Wire range : 30~10AWG

IEC Standard

- 1.Rated voltage/current : 400V / 24A
- 2.Torque value : M3.5 , 0.8N·m
- 3.Wire range : 0.2~4mm²

NOTES2:


- 1.Dimension shall be interpreted per ASME Y14.5-2009
- 2.Pitch : 6.1mm, Poles : N=01P
- 3.Stripping length : 8mm
- 4.Withstanding voltage : AC2500V/1Min
- 5.Operating temperature: -40°C~+105°C
- 6.Undimensioned tolerances:

Pitch range in mm		Nominal dimension range in mm				-	∩	□
TO	Over	TO	Over	TO	Over	TO	Over	TO
6	6 TO 10	10 TO 24	30 TO 60	60 TO 100	100 TO 150	150	150	150
±0.15	±0.20	±0.30	±0.30	±0.50	±0.70	±1.00	±1.30	±2'

7.RoHS Compliance

DG4 - 01P - 1Y - 00A (H)

(Series No.) (Poles) (Single Pitch) (Color): 1.(Grey)
2.(Blue)
3.(Black)
4.(Green)
5.(Orange)
6.(Red)
7.(Transparent)
8.(Yellow)
9.(White)



Card slot size VIEW

DETACHED LISTS	PART NO.:	/				NINGBO DEGSON ELECTRICAL CO., LTD			
	APPD:	/				NAME: DG4-01P-1Y-00A(H)			
	CHKD:	/				TITLE: CUSTOMER DRAWING			
	DRFT:	/				DRAWING NO.: /		REV	DO
THIRD ANGLE PROJECTION		MM (INCH)		DO NOT SCALE DRAWING		SHEET		1/1	
						SCALE		1:1	