

Наимен.	тип	$U_{кбо(и)}, В$	$U_{кэо(и)}, В$	$I_{кmax(и)}, мА$	$P_{кmax(т)}, Вт$	$n_{21э}$	$I_{кбо}, мкА$	$f_{гр.}, МГц$	$K_{ш}, Дб$
КТЗ102А	n-p-n	50	50	100(200)	0.25	100-200	≤ 0.05	≥ 150	≤ 10
КТЗ102Б		50	50	100(200)	0.25	200-500	≤ 0.05	≥ 150	≤ 10
КТЗ102В		30	30	100(200)	0.25	200-500	≤ 0.015	≥ 150	≤ 10
КТЗ102Г		20	20	100(200)	0.25	400-1000	≤ 0.015	≥ 150	≤ 10
КТЗ102Д		30	30	100(200)	0.25	200-500	≤ 0.015	≥ 150	≤ 4
КТЗ102Е		20	20	100(200)	0.25	400-1000	≤ 0.015	≥ 150	≤ 4
КТЗ102Ж		20	20	100(200)	0.25	100-250	≤ 0.05	≥ 150	-
КТЗ102И		20	20	100(200)	0.25	200-500	≤ 0.05	≥ 150	-
КТЗ102К		20	20	100(200)	0.25	200-500	≤ 0.015	≥ 150	-

Корпус:

